



## When can I use this Safety Cage?

This product should only be used exceptionally when it is used with machinery not designed for lifting persons as established in the European Directive 89/655/EEC and 95/63/EC. Those exceptional situations are:

- Technically impossible to use standard equipment designed to lift people.
- The risks arising from the environment in which the work is carried out or from the need to use auxiliary means on board the passenger compartment of lifting machines are greater than it would be the case of the use of load lifting machines to lift people.
- Emergency situations, such as; Evacuation of people, immediate repair to avoid a serious and imminent risk situation, etc.

	SWL	PEOPLE	SIZE	TARE
BA-164	750 KG	5	2400 x 2000 x 2045	1150 Kg
BA-164 GRAB	750 KG	5	4000 x 2000 x 2000	3500 Kg
BA-164 RESCUE	650 KG	4	2315 x 1265 x 2020	1100 Kg
BA-164B	240 KG	2	1620 x 1220 x 2000	650 Kg

## Rules and Regulations

- European Directive 2001/95/CE
- European Directive 2009/104/CE
- **Norm UNE EN 14502-1:2010**
- ICHCA: Container Top Safety Rsearch (Paper 4-1999)
- ICHCA: Safe Working on Container Ships (1994)
- ILO Code of Practice for Safety and Health in dock (2005)
- Lr's Code for Lifting Apliances in marine environment (2009)
- European Norm EN-795 "Personal fall protection equipment"
- INSST NTP 956 "Plataformas para elevación de personas acopladas a equipos de elevación de cargas"



This safety cage can be delivered inside a 40ft HC Contianer.

